

GARTEC 1000 PLATFORM LIFT

The Gartec 1000 Platform Lift is suited for passengers, wheelchair users, bikes and goods.

ABOUT

The Gartec 1000 platform lift is a 1,000kg platform lift, suitable for passengers, wheelchair users, bikes and goods movement. Availability to carry 1,000kg up to 13m travel, with doors on up to three sides. Optional extras give you design freedom, including larger doorways for powered wheelchairs and stretcher beds. No head fixing, no separate machine room and quick installation make the Gartec 1000 platform lift ideal for most environments.

FEATURES

- No head fixing required
- Up to 1000kg capacity
- Shaft supplied with the lift
- Solid RAL panels and glass panels optional
- Glass or fire rated doors
- Single press on landings
- Constant pressure on internal controls
- 110mm pit
- Call and send facility (goods only)

SUITABLE APPLICATIONS

The Gartec 1000 is ideal for bike showrooms, warehouses, offices with frequent goods movement. It can be used for up to 13-person passenger movement, so it is ideal for retail, care homes and healthcare (compliant to class 3 healthcare platform sizes). Contact us for further information.

TECHNICAL DETAILS

Type of Lift	Internal platform lift for public and commercial environments
Usage	Passenger/ goods platform lift
Environment	Internal only
Capacity	1000kg
Travel*	Up to 13,000 mm
No. of Floors	2-7
Top Height	2400mm (minimum) no head fixing required
Rated Speed	0.15m/s
Drive System	Screw and nut system with emergency battery backup
Platform Controls	Constant pressure operation
Landing Controls	Single press operation
Power Required	400v, 3-phase, 20A, soft stop-start (1000kg)
Shaft	Supplied, self-supporting glass or solid panels
Doors	Fully glazed, swing door as standard, doors can be on 3 sides, other options include vision panel and fire rated EI60
Door Configuration	Doors can be on 3 sides, but max 2 doors per floor
Compliance	EN81-41, Machinery Directive Compliant, Part M Compliant Class III Healthcare (sizes)

OPTIONS & EXTRAS

Doors

Panoramic glass door, EI60 fire rated door, optional automatic door opener, optional widened door (1300mm)

Mirrors

Optional mirror on cabin wall

Shaft

Steel panels in white (RAL 9010) as standard, optional full glass panels, other RAL colours available upon request

Security

Overload protection, safety edges and battery backup power as standard, optional key locking to landing doors and platform

Communicate

Alarm button with autodialler on platform as standard, intercom or autodialler with GSM (optional)

Destination

LED cabin display, LED landing display (optional), voice announcement (optional)


Flooring

Black rubber flooring as standard and aluminium checker plate optional


Buttons

Tactile & braille floor buttons with illumination as standard

PLAN VIEWS



CONFIGURATION



Configure your lift with doors on up to 3 sides over the whole travel of the lift.

NOTE: Maximum of 2 doors per floor can be installed

DIMENSIONS

Platform Size	Total Footprint
1400 x 2500mm	1860 x 2610mm
1400 x 2000mm	1860 x 2110mm
1100 x 2200mm	1560 x 2310mm

PLEASE NOTE: 55 Other platform sizes available upon request

